


# FL 630 ULTRA

<b>TIRE SIZE</b>	<b>600/50 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 D ; 170 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94054220	<b>RC (IN)</b>	139.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-003960
<b>SLR (IN)</b>	20.4		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2820	3260	3690	4450	5190	5910	6660	7340	8090	8780
40	3090	3570	4060	4890	5700	6500	7300	8070	8870	9640
30	3740	4320	4910	5950	6890	7880	8820	9740	10750	11670
25	4230	4890	5560	6700	7800	8930	10040	11070	12170	13230
15	4880	5640	6400	7740	8990	10310	11490	12790	14030	15240
5	5560	6430	7300	8820	10250	11740	13090	14550	15970	17360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.