


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 6.00 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO |
| VERSIONE | HD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 91 A8 |
| LI/SS FREE ROLLING | 103 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 164 | RIM REC | 4.00 E |
| OD (MM) | 735 | RIM ALT | 4.50 E; 4½ K |
| SLR (MM) | 343 | ECE | E11-106R-005195 |
| RC (MM) | 2190 | PR | 8 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 |
|------------|------|
| 10 FR | 1225 |
| 25 FR | 1040 |
| 30 FR | 980 |
| 40 FR | 875 |
| 10 DW | 860 |
| 25 DW | 730 |
| 30 DW | 690 |
| 40 DW | 615 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.