


# AT 603

|                           |  |
|---------------------------|--|
| <b>TYRE SIZE</b>          | <b>10.5/80 - 18</b>  |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY /<br>IMPLEMENTS  |
| <b>VERSION</b>            | SPECIAL  |
| <b>TYRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 119 A8   |
| <b>LI/SS FREE ROLLING</b> | 131 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94019670 | <b>RC (IN)</b> | 107.4           |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | W 9             |
| <b>OD (IN)</b>  | 35.7     | <b>RIM ALT</b> | W 8; 9          |
| <b>SLR (IN)</b> | 16.6     | <b>ECE</b>     | E11-106R-004546 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 54   |
|-----------|------|
| 5 FR      | 6020 |
| 15 FR     | 5110 |
| 20 FR     | 4820 |
| 25 FR     | 4300 |
| 5 DW      | 4200 |
| 15 DW     | 3570 |
| 20 DW     | 3360 |
| 25 DW     | 3000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.