

# COMMANDER (F)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>6.00 - 16</b>      |
| <b>UM</b>           | IS STANDARD           |
| <b>CONSTRUCTION</b> |                       |
| <b>MACHINERY</b>    | 2WD TRACTOR / TRACTOR |
| <b>VERSION</b>      | STANDARD              |
| <b>TIRE TYPE</b>    | TT                    |
| <b>LI/SS</b>        | 94 A6                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 175  | <b>RIM REC</b> | 4.50 E          |
| <b>OD (MM)</b>  | 750  | <b>RIM ALT</b> | 4.00 E; 5.00 F  |
| <b>SLR (MM)</b> | 357  | <b>ECE</b>     | E11-106R-003001 |
| <b>RC (MM)</b>  | 2308 | <b>PR</b>      | 8               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.50</b> |
| 30                | 670         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.