


# AGRIMAX RT 855

<b>TYRE SIZE</b>	250/85 R 22
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94062058	<b>RC (IN)</b>	116.7
<b>SW (IN)</b>	9.9	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	38.8	<b>RIM ALT</b>	W 7
<b>SLR (IN)</b>	17.8	<b>ECE</b>	E11-106R-002973

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.