



US standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 57



PRODUCT DATA SHEET



Radial



# EARTHMAX SR 57

RADIAL OTR TIRES

EARTHMAX SR 57 is an All Steel radial tire specially engineered for loaders, dozers and utility vehicles operating in underground mines. The tire provides superior traction, stability and comfort on severe and rocky surfaces. The L-5 extra deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to extraordinary resistance to rock cuts, and punctures.

### Technologies



All Steel



Block Pattern

### Performance



Durability



Traction



Cut Resistance



Stability

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 15"	94051687	7.50 R 15	TT	*	-	CRC	L-5	-	33.3	8.8	-	-	58	120	6.00	6.50
	94052783	8.25 R 15	TT	*	-	CRC	L-5	-	34.6	9.4	-	-	59	141	6.50	7.00
	94065615	10.00 R 15	TT	*	-	CRC	L-5	-	36.1	10.9	-	-	60	170	7.50	7.00
Ø 20"	94073290	10.00 R 20	TT	*	-	CRC	L-5	-	43.5	10.7	-	-	60	236	7.50	-
	94057160	12.00 R 20	TT	*	-	CRC	L-5	-	46.5	12.5	-	-	71	303	8.50	-
Ø 25"	94063307	18.00 R 25	TL	**	204 A2	CRC	L-5	-	65.0	20.3	-	-	101	1034	13.00/ 2.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference