

# AS 504

<b>TIRE SIZE</b>	<b>16.5/85 - 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8
<b>LI/SS FREE ROLLING</b>	163 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	415	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1325	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (MM)</b>	584	<b>ECE</b>	E11-106R-003512
<b>RC (MM)</b>	4013	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.80</b>
10 FR	6825
25 FR	5800
30 FR	5460
40 FR	4875
10 DW	4830
25 DW	4105
30 DW	3865
40 DW	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.