

# AW 702

<b>TIRE SIZE</b>	11.5/80 - 15.3
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	131 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94009367	<b>RC (IN)</b>	97.4
<b>SW (IN)</b>	11.7	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	33.2	<b>ECE</b>	E4-106R-001893
<b>SLR (IN)</b>	14.6	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>49</b>
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.