

MP 567

| | |
|---------------------------|---|
| TIRE SIZE | 12.0/75 - 18 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO / VEICULO UNIVERSAL |
| VERSÃO | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 126 A8 |
| LI/SS FREE ROLLING | 139 A8 |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 298 | RIM REC | W 9 |
| OD (MM) | 915 | RIM ALT | 9; 11 |
| SLR (MM) | 426 | ECE | E11-106R-006701 |
| RC (MM) | 2723 | PR | 12 |

LOAD CAPACITY (KG/TIRE)

| | |
|-------------------|-------------|
| KM/H / BAR | 4.00 |
| 40 FR | 2430 |
| 40 DW | 1700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.