


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 650/65 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	169 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94059225	<b>RC (IN)</b>	216.9
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	72.0	<b>ECE</b>	E11-106R-005103
<b>SLR (IN)</b>	32.7	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5460	6390	7320	8130	8950	9640	10800	11630
<b>FROM 40 TO 25</b>	6010	7030	8050	8950	9840	10600	11880	12790
20	6240	7310	8370	9300	10230	11020	12360	13290
12	6480	7590	8690	9660	10630	11440	12830	13800
5	7630	8930	10220	11360	12500	13460	15090	16240
<b>UPTO 20 CYC</b>	7800	9140	10460	11630	12790	13780	15440	16620
<b>UPTO 10 CYC</b>	9300	10890	12470	13870	15260	16430	18410	19820
<b>UPTO 5 CYC</b>	10210	11950	13680	15210	16730	18020	20190	21740
10HT	6240	7310	8370	9300	10230	11020	12360	13290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.