

# FLOTATION 648

<b>TIRE SIZE</b>	<b>400/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	144 A8/140 B
<b>LI/SS FREE ROLLING</b>	156 A8/152 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	AG 11.75
<b>OD (MM)</b>	1070	<b>ECE</b>	E4-106R-002336
<b>SLR (MM)</b>	475	<b>PR</b>	16
<b>RC (MM)</b>	3233		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	2.50	3.50
10 FR	3410	4600	5600
20 FR	3070	4140	5040
30 FR	2725	3680	4480
40 FR	2435	3285	4000
50 FR	2190	2955	3550
10 DW	2385	3220	3920
20 DW	2150	2900	3530
30 DW	1910	2575	3135
40 DW	1705	2300	2800
50 DW	1535	2070	2500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.