

# AGRIMAX V-FLECTO

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TYRE SIZE</b>    | <b>VF 580/85 R 46 CFO</b>                                                                |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / HIGH-POWER TRACTOR                                                             |
| <b>VERSION</b>      | SPECIAL                                                                                  |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 179 D                                                                                    |



## DIMENSIONS IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 605  | <b>RIM REC</b> | DW 20 B          |
| <b>OD (MM)</b>  | 2156 | <b>RIM ALT</b> | DW 21 B, DW18L   |
| <b>SLR (MM)</b> | 947  | <b>ECE</b>     | E11-106R-0011691 |
| <b>RC (MM)</b>  | 6451 | <b>SRI</b>     | 1025             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR           | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6   | 2     |
|----------------------|------|------|------|------|------|-------|-------|
| <b>70</b>            | 3530 | 4095 | 4660 | 5295 | 5860 | 6425  | 7055  |
| <b>FROM 65 TO 40</b> | 3875 | 4495 | 5115 | 5815 | 6435 | 7055  | 7750  |
| <b>30</b>            | 3955 | 4585 | 5220 | 5930 | 6565 | 7195  | 7905  |
| <b>20</b>            | 4030 | 4675 | 5320 | 6045 | 6690 | 7335  | 8060  |
| <b>10</b>            | 4265 | 4945 | 5630 | 6395 | 7080 | 7760  | 8525  |
| <b>10HT</b>          | 3955 | 4585 | 5220 | 5930 | 6565 | 7195  | 7905  |
| <b>UPTO 10 CYC</b>   | 5755 | 6680 | 7600 | 8635 | 9555 | 10475 | 11510 |
| <b>UPTO 15 CYC</b>   | 5255 | 6095 | 6935 | 7880 | 8720 | 9560  | 10505 |
| <b>UPTO 30 CYC</b>   | 4400 | 5105 | 5810 | 6600 | 7305 | 8010  | 8800  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.