

AGRIMAX V- FLECTO

TYRE SIZE	VF 380/85 R 34
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	160 D



DIMENSIONS US STANDARD

USA CODE	94523023	RIM REC	W 13
SW (IN)	15.35	RIM ALT	W 11
OD (IN)	59.44	ECE	E11-106R-0012141
SLR (IN)	26.77	TREAD DEPTH (32nd)	55.43
RC (IN)	177.59		

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	3870	4560	5260	5850	6550	7140	7840	8430	9230	9920
FROM 40 TO 25	3870	4560	5260	5850	6550	7140	7840	8430	9230	9920
20	3960	4660	5370	5970	6680	7290	8000	8610	9410	10120
12	4030	4750	5480	6100	6810	7430	8160	8770	9600	10320
5	4270	5030	5790	6450	7210	7860	8630	9280	10150	10910
*UPTO 5 CYC WITH FRONT LOADER	5750	6790	7810	8700	9730	10610	11650	12530	13710	14740
10HT	3960	4660	5370	5970	6680	7290	8000	8610	9410	10120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.