

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>480/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1478	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (MM)</b>	659	<b>ECE</b>	E11-106R-005522
<b>RC (MM)</b>	4372	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1420	1650	1880	2115	2345	2575
50	1490	1735	1975	2220	2465	2705
40	1555	1805	2060	2315	2570	2820
30	1635	1900	2165	2435	2700	2965
10 LT	1905	2215	2525	2835	3145	3455
10 HT	1635	1900	2165	2435	2700	2965

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.