


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/65 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	163 D



DIMENSIONS IS STANDARD

SW (MM)	597	RIM REC	DW 21 B
OD (MM)	1491	RIM ALT	DW 20 B
SLR (MM)	655	ECE	E11-106R-007602
RC (MM)	4453	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.8	2.0
70	2265	2620	2975	3375	3690	4000	4440
FROM 65 TO 40	2490	2880	3270	3705	4050	4390	4875
30	2540	2940	3335	3785	4130	4480	4975
20	2590	2995	3400	3855	4210	4565	5070
10	2740	3170	3595	4080	4455	4830	5365
*UPTO 10 CYC WITH FRONT LOADER	3485	4030	4575	5190	5665	6145	6825
10 HT	2540	2940	3335	3785	4130	4480	4975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.