


# AGRIMAX SPARGO

**VF 320/90 R 54**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	168 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	323	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1948	<b>RIM ALT</b>	W 10; DW 10; W 10 L; DW 11
<b>SLR (MM)</b>	910	<b>ECE</b>	E11-106R-009070
<b>RC (MM)</b>	5946	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
<b>70</b>	2230	2490	2800	3060	3215	3370	3475	3575	3760	3940	4095	4250	4380	4510	4640	4770	4975	5180
<b>FROM 65 TO 40</b>	2410	2690	3025	3305	3475	3640	3755	3865	4060	4260	4425	4595	4735	4875	5015	5155	5380	5600
<b>30</b>	2460	2745	3090	3375	3545	3715	3830	3945	4145	4345	4515	4690	4830	4975	5115	5260	5490	5715
<b>20</b>	2505	2800	3150	3440	3615	3790	3905	4020	4225	4430	4605	4780	4925	5070	5215	5360	5595	5825
<b>10</b>	2650	2960	3330	3635	3820	4005	4130	4255	4470	4685	4870	5055	5210	5360	5515	5670	5915	6160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.