

# XL GRIP (BHL)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | 10.00 - 20            |
| <b>UM</b>           | IS STANDARD           |
| <b>CONSTRUCTION</b> | ❖ BIAS                |
| <b>MACHINERY</b>    | BAGGERLADER           |
| <b>VERSION</b>      | ARAMID + STEEL BELTED |
| <b>TIRE TYPE</b>    | TT                    |



## ABMESSUNGEN IS STANDARD

|                 |      |                |     |
|-----------------|------|----------------|-----|
| <b>OD (MM)</b>  | 1075 | <b>RIM ALT</b> | 7.0 |
| <b>SLR (MM)</b> | 505  | <b>PR</b>      | 18  |
| <b>RC (MM)</b>  | 3257 |                |     |
| <b>RIM REC</b>  | 7.5  |                |     |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>8.30</b> | <b>7.60</b> |
|-------------------|-------------|-------------|
| 10                | 4480        | -           |
| 40                | -           | 3305        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.