


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 16.0/70 - 20 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 135 A8 |
| LI/SS FREE ROLLING | 147 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------|
| SW (MM) | 418 | RIM REC | 13 |
| OD (MM) | 1097 | RIM ALT | 12 SDC; 14; 13 SDC |
| SLR (MM) | 487 | ECE | E4-106R-001875 |
| RC (MM) | 3214 | PR | 10 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.50 |
|------------|------|
| 10 FR | 4305 |
| 25 FR | 3660 |
| 30 FR | 3445 |
| 40 FR | 3075 |
| 10 DW | 3050 |
| 25 DW | 2595 |
| 30 DW | 2440 |
| 40 DW | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.