

# AGRIMAX RT 657

**480/65 R 24****UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** ÜZÜM HASAT MAKINESİ / TRAKTÖR /  
BIÇERDÖVER**VERSION** STANDARD**TIRE TYPE** TL

140 D ; 143 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94028528	<b>RC (IN)</b>	146.9
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	48.6	<b>RIM ALT</b>	W 14 L
<b>SLR (IN)</b>	22.1	<b>ECE</b>	E4-106R-000617

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2650	3090	3470	3860	4240	4570	5070	5510
30	2780	3240	3650	4060	4460	4810	5320	5790
25	2890	3370	3790	4210	4630	4990	5530	6010
20	3040	3550	4000	4440	4880	5270	5830	6340
5 LT	3550	4140	4660	5170	5690	6140	6800	7390
5 HT	3040	3550	4000	4440	4880	5270	5830	6340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.