


# AS 504

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	106 A8
<b>LI/SS FREE ROLLING</b>	119 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94018536	<b>RC (IN)</b>	94.6
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	30.9	<b>ECE</b>	E11-106R-003509
<b>SLR (IN)</b>	14.2	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.