


MULTIMAX MP 522

TIRE SIZE	480/80 R 26 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	167 A8/B



DIMENSIONER IS STANDARD

SW (MM)	479	RIM REC	DW 15 L
OD (MM)	1428	RIM ALT	DW 16 L
SLR (MM)	638	ECE	E11-106R-008146
RC (MM)	4287	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
50	2575	2815	3055	3295	3540	3780	4020	4260	4500	4740	4975	5215	5450	-	-
40	2575	2815	3055	3295	3540	3780	4020	4260	4500	4740	4975	5215	5450	-	-
30	2790	3045	3300	3550	3805	4060	4315	4565	4820	5075	5330	5580	5835	-	-
25	2890	3155	3420	3680	3945	4210	4475	4735	5000	5265	5525	5790	6050	-	-
10 CYC.	3200	3555	3910	4265	4620	4975	5330	5685	6040	6395	6750	7460	8175	-	-
STATIC	4900	5445	5990	6535	7080	7625	8170	8715	9260	9805	10350	10895	11445	11990	12535

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.