

# LG RIB

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>13X5.00 - 6</b>                                |
| <b>UM</b>           | US STANDARD                                       |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | MAQUINA DE CORTAR RELVA / TRATOR PEQUENO / TRATOR |
| <b>VERSÃO</b>       | ARAMID BELTED                                     |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94013012 | <b>RC (IN)</b> | 37.1            |
| <b>SW (IN)</b>    | 5.0      | <b>RIM REC</b> | 3.50 A          |
| <b>OD (IN)</b>    | 12.8     | <b>ECE</b>     | E11-106R-005221 |
| <b>SLR (IN)</b>   | 5.7      | <b>PR</b>      | 6               |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 10               | 560       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.