

AGRIMAX RT 765



AGRIMAX
RADIAL TRACTOR TIRES

AGRIMAX RT 765



AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.



SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
Ø16"	220/70 R 16	99 A8/B	W 7 W 8	8.7	28.1	12.8	84.4	340	STD
	200/70 R 16	94 A8/B	W 6 W 7	7.8	27.0	12.4	81.1	330	STD
	240/70 R 16	104 A8/B	W 8 W 8 L W 9 L	9.6	29.2	13.2	85.7	350	STD
	280/70 R 16	112 A8/B	W 9 W 8 W 8 L W 10	11.1	31.4	14.0	93.3	380	STD
	260/70 R 16	109 A8/B	W 8 W 8 L W 9 L	10.2	30.3	13.6	89.9	370	STD

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1W	 180 lbs	  	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø18"	280/70 R 18	114 A8/B	W 9	W 8 W 10	10.8	33.4	15.0	100.3	400	STD
Ø20"	360/70 R 20	129 A8/B	W 11	W 10 W 12	14.1	41.0	18.5	122.9	475	STD
	280/70 R 20	116 A8/B	W 9	W 8 W 10	10.8	35.4	16.1	106.5	450	STD
	280/70 R 20	116 A8/B	W 9	W 8 W 10	10.8	35.4	16.1	106.5	450	SPL
	260/70 R 20	113 A8/B	W 8	9 W 9	10.2	34.3	15.8	103.9	425	SPL
	380/70 R 20	132 A8/B	W 12	W 11 W 13	15.0	42.6	19.0	126.5	525	STD
	320/70 R 20	123 A8/B	W 10	W 9 W 11	12.6	38.7	17.5	115.7	475	STD
	260/70 R 20	113 A8/B	W 8	9 W 9	10.2	34.3	15.8	103.9	425	STD
	300/70 R 20	120 A8/B	W 9	W 10	11.6	37.5	16.9	112.4	450	STD
Ø24"	380/70 R 24	125 D	W 12	W 11 W 13	15.0	46.9	21.2	140.2	575	STD

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
			
			

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
360/70 R 24	122 D	W 11	W 10 W 12	14.1	45.4	20.4	133.7	550	STD
420/70 R 24	134 D	W 13	W 12 W 14 L	16.5	49.1	21.8	144.9	600	STD
420/70 R 24	130 D	W 13	W 12 W 14 L	16.5	49.1	21.8	144.9	600	STD
420/70 R 24	134 D	W 13	W 12 W 14 L	16.5	49.1	21.8	144.9	600	SPL
420/70 R 24	130 D	W 13	W 12 W 14 L	16.5	49.1	21.8	144.9	600	SPL
360/70 R 24	122 D	W 11	W 10 W 12	14.1	45.4	20.4	133.7	550	SPL
320/70 R 24	116 D	W 10	W 9 W 11	12.6	43.1	19.8	127.8	525	SPL
320/70 R 24	116 D	W 10	W 9 W 11	12.6	43.1	19.8	127.8	525	STD
480/70 R 24	138 D	W 15 L	W 14 L W 16 L	18.9	51.8	22.8	153.3	625	SPL
380/70 R 24	125 D	W 12	W 11 W 13	15.0	46.9	21.2	140.2	575	SPL

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
D	180 lbs		
Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	480/70 R 24	138 D	W 15 L	W 14 L W 16 L	18.9	51.8	23.0	153.5	625	STD
Ø28"	360/70 R 28	125 D	W 11	W 10 W 12	14.1	49.3	22.8	148.3	600	SPL
	480/70 R 28	140 D	W 15 L	W 14 L W 16 L	18.9	55.9	25.0	164.8	675	STD
	420/70 R 28	133 D	W 13	W 12 W 14 L	16.5	53.1	23.8	158.3	650	SPL
	600/70 R 28	157 D	DW 18 L	DW 20 B	23.3	61.1	27.4	184.7	725	STD
	420/70 R 28	133 D	W 13	W 12 W 14 L	16.5	53.1	23.8	158.3	650	STD
	360/70 R 28	125 D	W 11	W 10 W 12	14.1	49.3	22.8	148.3	600	STD
	380/70 R 28	127 D	W 12	W 11 W 13	15.0	50.9	23.1	152.9	625	SPL
	380/70 R 28	127 D	W 12	W 11 W 13	15.0	50.9	23.1	152.9	625	STD
	480/70 R 28	140 D	W 15 L	W 14 L W 16 L	18.9	55.9	25.0	164.8	675	SPL

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
D	180 lbs		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø30"	420/70 R 30	134 D	W 13	W 12 W 14 L	16.5	55.0	24.8	164.3	675	STD
	600/70 R 30	152 D	DW 20 B	DW 18 L W 18 L	24.1	63.1	28.0	188.0	750	SPL
	600/70 R 30	152 D	DW 20 B	DW 18 L W 18 L	24.1	63.1	28.0	188.0	750	STD
	480/70 R 30	141 D	W 15 L	W 14 L W 16 L	18.9	58.2	25.9	172.1	700	SPL
	480/70 R 30	141 D	W 15 L	W 14 L W 16 L	18.9	58.2	25.9	172.1	700	STD
	420/70 R 30	134 D	W 13	W 12 W 14 L	16.5	55.0	24.8	164.3	675	SPL
Ø34"	520/70 R 34	148 D	W 16 L	W 15 L W 18 L	20.3	64.6	29.1	194.0	775	SPL
	480/70 R 34	149 D	W 15 L	W 14 L W 16 L	18.9	62.2	28.0	187.9	750	SPL
	520/70 R 34	148 D	W 16 L	W 15 L W 18 L	20.3	64.6	29.1	194.0	775	STD
	480/70 R 34	149 D	W 15 L	W 14 L W 16 L	18.9	62.2	28.0	187.9	750	STD

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1W	 D	 180 lbs	

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
480/70 R 34	155 D	W 15 L	W 14 L W 16 L	18.9	62.2	28.7	188.5	750	SPL
480/70 R 34	155 D	W 15 L	W 14 L W 16 L	18.9	62.2	28.7	188.5	750	STD
Ø38"	580/70 R 38	180 D	W 18 L DW 18 L DD 18 L	22.7	71.9	32.3	216.7	875	SB
	480/70 R 38	145 D	W 15 L W 14 L W 16 L	18.9	66.2	30.1	199.0	800	SPL
	710/70 R 38	175 D 178 A8	DW 23 B	-	28.2	77.1	33.8	226.4	SPL
	650/75 R 38	169 D	DW 21 B DW 20 B DW 23 B	25.8	76.4	34.4	229.1	925	STD
	710/70 R 38	175 D 178 A8	DW 23 B	-	28.2	77.1	33.8	226.4	STD
	710/70 R 38	166 D	DW 23 B	-	28.2	77.1	33.8	226.4	SPL
	480/70 R 38	145 D	W 15 L W 14 L W 16 L	18.9	66.2	30.1	199.0	800	STD
	620/70 R 38	170 D	DW 20 B DW 18 L W 18 L	24.6	72.2	32.6	220.1	875	STD

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
D	180 lbs		

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
520/70 R 38	150 D	W 16 L	W 15 L W 18 L	20.3	68.9	31.2	208.7	825	STD
620/70 R 38	170 D	DW 20 B	DW 18 L W 18 L	24.6	72.2	32.6	220.1	875	SPL
520/70 R 38	150 D	W 16 L	W 15 L W 18 L	20.3	68.9	31.2	208.7	825	SPL
580/70 R 38	155 D	W 18 L	-	22.7	71.9	32.3	215.4	875	SPL
580/70 R 38	155 D	W 18 L	-	22.7	71.9	32.3	215.4	875	STD
Ø42"	620/70 R 42	160 D	DW 20 B DW 18 L	24.6	76.2	34.5	226.1	925	STD
	620/70 R 42	160 D	DW 20 B DW 18 L	24.6	76.2	34.5	226.1	925	SPL
	710/70 R 42	176 D 179 AB	DW 23 B DW 25 B	28.2	81.1	36.3	243.1	975	SPL
	620/70 R 42	166 D	DW 20 B DW 18 L	24.6	76.2	34.5	228.4	925	SPL
	650/75 R 42	170 D	DW21B DW20B DW23B	25.8	80.4	36.1	242.0	975	STD

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
D		180 lbs	
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION	
		REC RIM	ALT RIM							
										
710/70 R 42	176 D 179 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	975	STD	
710/70 R 42	173 D 176 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	975	STD	
620/70 R 42	173 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.5	925	STD	
620/70 R 42	173 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.5	925	SPL	
620/70 R 42	166 D	DW 20 B	DW 18 L	24.6	76.2	34.5	228.4	925	STD	
Ø46"	620/70 R 46	162 D	DW 20 B	-	24.6	80.2	36.4	240.4	975	STD
	620/70 R 46	162 D	DW 20 B	-	24.6	80.2	36.4	240.4	975	SPL

STD: STANDARD, SB: STEEL BELTED, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			