


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 360/70 R 18 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 142 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------------------------|
| SW (MM) | 360 | RIM REC | 11 |
| OD (MM) | 969 | RIM ALT | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC |
| SLR (MM) | 439 | ECE | E11-106R-002996 |
| RC (MM) | 2887 | SRI | 475 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 1275 | 1515 | 1725 | 1965 | 2200 | 2360 | 2650 | - | - |
| 40 | 1275 | 1515 | 1725 | 1965 | 2200 | 2360 | 2650 | - | - |
| 30 | 1365 | 1620 | 1850 | 2105 | 2360 | 2530 | 2840 | - | - |
| 25 | 1415 | 1680 | 1915 | 2180 | 2445 | 2625 | 2945 | - | - |
| 10 CYC. | 1555 | 1910 | 2250 | 2585 | 2945 | 3200 | 3620 | 3820 | 3975 |
| STATIC | 2380 | 2930 | 3445 | 3965 | 4515 | 4910 | 5550 | 5855 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.