

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	158 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94021826	<b>RC (IN)</b>	231.1
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 A ; W 16 A ; DD 16
<b>OD (IN)</b>	76.2	<b>RIM ALT</b>	W 16 L ; DD 16 L ; DW 16 L
<b>SLR (IN)</b>	35.2	<b>ECE</b>	E4-106R-001731

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	4410	5060	5810	6560	7310	8060	8720	9350
25	4410	5060	5810	6560	7310	8060	8720	9350
20	4720	5420	6230	7020	7830	8630	9340	10030
5 LT	5910	6790	7790	8800	9800	10800	11680	12550
5 HT	4720	5420	6230	7020	7830	8630	9340	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.