

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 140 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1421 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 634 | ECE | E11-106R-005521 |
| RC (MM) | 4185 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1375 | 1600 | 1825 | 2050 | 2275 | 2500 |
| 50 | 1445 | 1680 | 1920 | 2155 | 2390 | 2625 |
| 40 | 1510 | 1755 | 2005 | 2250 | 2495 | 2740 |
| 30 | 1585 | 1840 | 2100 | 2360 | 2620 | 2875 |
| 10 LT | 1845 | 2145 | 2450 | 2750 | 3050 | 3350 |
| 10 HT | 1585 | 1840 | 2100 | 2360 | 2620 | 2875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.