

AGRIMAX RT 657

TIRE SIZE	440/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	138 D ; 141 A8



DIMENSIONI US STANDARD

CODICE USA	94029143	RC (IN)	154.6
SW (IN)	17.4	RIM REC	W 14 L
OD (IN)	50.5	RIM ALT	W 13 ; W 15 L
SLR (IN)	23.2	ECE	E4-106R-000767

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2500	2920	3280	3650	4010	4320	4790	5200
30	2630	3060	3450	3840	4210	4540	5040	5470
25	2730	3190	3580	3980	4380	4720	5220	5680
20	2880	3360	3780	4200	4620	4970	5510	5990
5 LT	3350	3910	4400	4890	5380	5800	6430	6980
5 HT	2880	3360	3780	4200	4620	4970	5510	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.