

# RIDEMAX FL 693 M



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>650/50 R 22.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | АВТОЦИСТЕРНА / ПРИЦЕП /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ                          |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 168 D  |

## РАЗМЕРЫ IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 645  | <b>RIM REC</b> | AG 20.00        |
| <b>OD (MM)</b>  | 1222 | <b>ECE</b>     | E11-106R-006489 |
| <b>SLR (MM)</b> | 535  | <b>SRI</b>     | 575             |
| <b>RC (MM)</b>  | 3715 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 5.0   |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 70         | 1480 | 1890 | 2295 | 2605 | 3010 | 3420 | 3775 | 4135 | 4540 | 5100  |
| 65         | 1625 | 2075 | 2520 | 2860 | 3305 | 3755 | 4145 | 4540 | 4985 | 5600  |
| 50         | 1970 | 2510 | 3080 | 3460 | 4005 | 4545 | 5020 | 5495 | 6035 | 6780  |
| 40         | 2210 | 2820 | 3465 | 3890 | 4500 | 5110 | 5640 | 6175 | 6785 | 7620  |
| 30         | 2455 | 3135 | 3845 | 4315 | 4995 | 5670 | 6265 | 6855 | 7530 | 8460  |
| 25         | 2570 | 3275 | 4020 | 4515 | 5225 | 5930 | 6550 | 7170 | 7880 | 8850  |
| 10         | 2925 | 3730 | 4580 | 5145 | 5950 | 6755 | 7460 | 8165 | 8975 | 10080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.