

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>240/70 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	104 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	244	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	742	<b>RIM ALT</b>	W 8 L ; W 9 L
<b>SLR (MM)</b>	335	<b>ECE</b>	E4-106R-000609
<b>RC (MM)</b>	2176	<b>SRI</b>	350

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	425	490	560	630	705	775	840	900
40	425	490	560	630	705	775	840	900
30	455	525	600	680	755	830	900	965
10 LT	570	655	755	850	945	1045	1130	1210
10 HT	455	525	600	680	755	830	900	965

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.