

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 710/55 R 34                                                                           |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR                                         |
| VERSIÓN      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 170 D                                                                                    |



## DIMENSIONES US STANDARD

|            |          |          |                 |
|------------|----------|----------|-----------------|
| CÓDIGO USA | 94059942 | RC (IN)  | 195.4           |
| SW (IN)    | 28.2     | RIM REC  | DW 25 B         |
| OD (IN)    | 64.8     | ECE      | E11-106R-005995 |
| SLR (IN)   | 29.4     | TRA CODE | R1W             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    | 41    |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 5050 | 5900  | 6610  | 7460  | 8300  | 9140  | 10230 | 10950 | 12040 |
| FROM 40 TO 25 | 5560 | 6480  | 7270  | 8200  | 9130  | 10050 | 11240 | 12040 | 13230 |
| 20            | 5780 | 6730  | 7560  | 8520  | 9490  | 10450 | 11680 | 12510 | 13760 |
| 12            | 6000 | 7000  | 7850  | 8850  | 9850  | 10850 | 12140 | 13000 | 14290 |
| 5             | 7050 | 8220  | 9240  | 10410 | 11580 | 12760 | 14270 | 15280 | 16800 |
| UPTO 20 CYC   | 7220 | 8420  | 9460  | 10660 | 11860 | 13060 | 14620 | 15640 | 17200 |
| UPTO 10 CYC   | 8610 | 10040 | 11280 | 12710 | 14140 | 15570 | 17430 | 18650 | 20500 |
| UPTO 5 CYC    | 9440 | 11010 | 12370 | 13930 | 15510 | 17080 | 19110 | 20460 | 22490 |
| 5 HT          | 5780 | 6730  | 7560  | 8520  | 9490  | 10450 | 11680 | 12510 | 13760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.