


# AS 504

<b>TIRE SIZE</b>	<b>6.5/80 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	72 A8
<b>LI/SS FREE ROLLING</b>	84 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	169	<b>RIM REC</b>	5 J
<b>OD (MM)</b>	608	<b>RIM ALT</b>	5 JA
<b>SLR (MM)</b>	283	<b>ECE</b>	E11-106R-003440
<b>RC (MM)</b>	1836	<b>PR</b>	4

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.40</b>
10 FR	700
25 FR	595
30 FR	560
40 FR	500
10 DW	495
25 DW	420
30 DW	400
40 DW	355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.