


FL 630 ULTRA

TIRE SIZE	710/50 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D ; 181 A8



ABMESSUNGEN IS STANDARD

SW (MM)	727	RIM REC	AG 24.00
OD (MM)	1383	RIM ALT	AG 20.00
SLR (MM)	599	ECE	E11-106R-006812
RC (MM)	4208	SRI	650

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1750	1995	2240	2785	3170	3660	4150	4535	4970	5460
65	1920	2190	2460	3060	3480	4020	4560	4980	5460	6000
50	2325	2650	2980	3705	4210	4865	5520	6025	6610	7260
40	2640	3015	3385	4210	4785	5530	6270	6850	7510	8250
25	3035	3465	3890	4835	5500	6355	7205	7870	8630	9480
10	3460	3945	4430	5510	6265	7240	8210	8965	9830	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.