

# AS 504

<b>TIRE SIZE</b>	<b>15.0/55 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	122 A8
<b>LI/SS FREE ROLLING</b>	134 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	380	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	890	<b>RIM ALT</b>	13
<b>SLR (MM)</b>	395	<b>ECE</b>	E4-106R-001571
<b>RC (MM)</b>	2608	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.