

# FLOTATION 648

<b>TIRE SIZE</b>	<b>500/50 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	140 A8/136 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1070	<b>PR</b>	12
<b>SLR (MM)</b>	475		
<b>RC (MM)</b>	3200		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2
70	3970	5060	5955	6945	7840	8930	9920
65	4360	5560	6540	7630	8615	9810	10900
50	5105	6510	7655	8930	10080	11480	12755
40	5630	7175	8440	9850	11115	12660	14065
10	7155	9120	10730	12520	14130	16095	17880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.