


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 480/65 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 140 D ; 143 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| CODE USA | 94062621 | RC (IN) | 146.9 |
| SW (IN) | 18.9 | RIM REC | W 15 L |
| OD (IN) | 48.6 | RIM ALT | W 14 L |
| SLR (IN) | 22.1 | ECE | E4-106R-000617 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2650 | 3090 | 3470 | 3860 | 4240 | 4570 | 5070 | 5510 |
| 30 | 2780 | 3240 | 3650 | 4060 | 4460 | 4810 | 5320 | 5790 |
| 25 | 2890 | 3370 | 3790 | 4210 | 4630 | 4990 | 5530 | 6010 |
| 20 | 3040 | 3550 | 4000 | 4440 | 4880 | 5270 | 5830 | 6340 |
| 5 LT | 3550 | 4140 | 4660 | 5170 | 5690 | 6140 | 6800 | 7390 |
| 5 HT | 3040 | 3550 | 4000 | 4440 | 4880 | 5270 | 5830 | 6340 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.