

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/50 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	157 A8/154 B
<b>LI/SS FREE ROLLING</b>	169 A8/165 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94006519	<b>RC (IN)</b>	161.4
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	24.00
<b>OD (IN)</b>	54.1	<b>ECE</b>	E4-106R-002278
<b>SLR (IN)</b>	24.4	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	26
<b>5 FR</b>	16090	16710	17900
<b>10 FR</b>	14480	15050	16110
<b>20 FR</b>	12870	13370	14320
<b>25 FR</b>	11500	11940	12790
<b>30 FR</b>	10350	10750	11350
<b>5 DW</b>	11450	11880	12730
<b>10 DW</b>	10310	10690	11460
<b>20 DW</b>	9160	9500	10180
<b>25 DW</b>	8180	8490	9090
<b>30 DW</b>	7360	7640	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.