

FLOTATION 648

TIRE SIZE	385/65 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDÉUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 156 B



DIMENSIONS US STANDARD

CODE USA	94006298	RC (IN)	127.3
SW (IN)	15.7	RIM REC	AG 11.75
OD (IN)	42.1	ECE	E4-106R-002263
SLR (IN)	18.7	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55	58	62
5 FR	12920	13320	13890
10 FR	11630	11980	12500
20 FR	10330	10660	11110
25 FR	9230	9510	9920
30 FR	8300	8560	8820
5 DW	9040	9330	9720
10 DW	8130	8390	8750
20 DW	7230	7450	7780
25 DW	6460	6660	6940
30 DW	5810	6000	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.