

AGRIMAX FORCE

TIRE SIZE	IF 710/60 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	172 D



DIMENSIONES IS STANDARD

SW (MM)	708	RIM REC	DW 25 B
OD (MM)	1817	ECE	E11-106R-004754
SLR (MM)	812	SRI	875
RC (MM)	5405	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2630	3030	3490	3890	3450	4750	5325	5730
FROM 65 TO 40	2895	3335	3840	4280	4785	5225	5855	6300
30	3010	3465	3990	4450	4975	5430	6085	6550
20	3125	3600	4145	4620	5165	5640	6320	6800
10	3675	4235	4875	5435	6075	6635	7435	8000
*UPTO 10 CYC WITH FRONT LOADER	4050	4665	5375	5990	6695	7315	8195	8820
10 HT	3010	3465	3990	4450	4975	5430	6085	6550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.