


AGRIMAX RT 765

| | |
|---------------------|---|
| TIRE SIZE | 360/70 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 122 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 357 | RIM REC | W 11 |
| OD (MM) | 1152 | RIM ALT | W 10; W 12 |
| SLR (MM) | 519 | ECE | E11-106R-005824 |
| RC (MM) | 3395 | SRI | 550 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 825 | 960 | 1095 | 1230 | 1365 | 1500 |
| 50 | 870 | 1010 | 1150 | 1295 | 1435 | 1575 |
| 40 | 905 | 1055 | 1205 | 1350 | 1500 | 1645 |
| 30 | 950 | 1105 | 1260 | 1415 | 1570 | 1725 |
| 10 LT | 1110 | 1290 | 1470 | 1650 | 1830 | 2010 |
| 10 HT | 950 | 1105 | 1260 | 1415 | 1570 | 1725 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.