


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 900/65 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STEEL BELTED SPL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	193 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94512713	<b>RC (IN)</b>	275.7
<b>SW (IN)</b>	35.4	<b>RIM REC</b>	DW 30B
<b>OD (IN)</b>	92.0	<b>ECE</b>	E11-106R-0010524
<b>SLR (IN)</b>	39.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	11760	13600	15450	17530	19150	20760	23070
<b>FROM 40 TO 25</b>	12930	14960	16990	19270	21040	22820	25350
20	13180	15260	17320	19640	21460	23270	25860
12	13440	15550	17660	20030	21880	23720	26370
5	14220	16450	18680	21190	23140	25100	27890
<b>UPTO 20 CYC</b>	14670	16960	19270	21860	23870	25890	28770
<b>UPTO 10 CYC</b>	17510	20260	23000	26100	28500	30910	34350
<b>UPTO 5CYC</b>	19190	22200	25220	28600	31240	33870	37640
5 HT	13180	15260	17320	19640	21460	23270	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.