


AW 711

TIRE SIZE	400/60 R 18
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HAY HARVESTER / IMPLEMENT MACHINERY / HARVESTER / IMPLEMENTS
VERSION	STUBBLE RESISTANT
TL/TT	TL
LI/SS	159 A8/B



DIMENSIONS IS STANDARD

SW (MM)	394	RIM REC	14
OD (MM)	945	RIM ALT	13
SLR (MM)	419	ECE	E4-106R-001397
RC (MM)	2807	SRI	450

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	3.8	4.0	5.0	5.5
50	1220	1585	1950	2235	2600	2965	3165	3490	3655	3815	4057	4375
40	1220	1585	1950	2235	2600	2965	3165	3490	3655	3815	4057	4375
30	1365	1775	2185	2500	2910	3320	3550	3910	4095	4275	4545	4900
25	1450	1885	2320	2660	3095	3530	3770	4155	4350	4545	4830	5210
20	1535	1995	2460	2815	3275	3735	3990	4400	4605	4810	5115	5515
10	1705	2220	2730	3125	3640	4150	4435	4885	5115	5340	5680	6125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.