

# D 404

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>8.25 - 16</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | МАЛОТОННАЖНЫЙ ГРУЗОВИК / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |        |
|-----------------|----------|----------------|--------|
| <b>USA CODE</b> | 94013807 | <b>RIM ALT</b> | 6.00 G |
| <b>SW (IN)</b>  | 9.4      | <b>PR</b>      | 8      |
| <b>OD (IN)</b>  | 33.8     |                |        |
| <b>RIM REC</b>  | 6.50 H   |                |        |

## LOAD CAPACITY (LBS/TIRE)

|                  |   |
|------------------|---|
| <b>MPH / PSI</b> | - |
| -                | - |
| -                | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.