


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>620/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94063369	<b>RC (IN)</b>	228.5
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	76.2	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	34.5	<b>ECE</b>	E11-106R-005833

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
<b>40</b>	5590	6590	7590	8450	9460	10320	11320	12180	13330	14330
<b>30</b>	5870	6920	7980	8880	9930	10840	11890	12800	14000	15050
<b>25</b>	6130	7230	8320	9270	10360	11310	12400	13350	14600	15700
<b>20</b>	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480
<b>5 LT</b>	7500	8840	10180	11330	12680	13830	15180	16320	17870	19200
<b>5 HT</b>	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.