


# AS 504

<b>TIRE SIZE</b>	<b>16.5/85 - 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8
<b>LI/SS FREE ROLLING</b>	168 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	415	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1325	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (MM)</b>	584	<b>ECE</b>	E4-106R-001877
<b>RC (MM)</b>	4013	<b>PR</b>	16

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80
10 FR	7840
25 FR	6665
30 FR	6270
40 FR	5600
10 DW	5425
25 DW	4610
30 DW	4340
40 DW	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.