


FORESTMAX

TIRE SIZE	540/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / FORESTRY
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	149 A8 ; 146 B



DIMENSIONS US STANDARD

USA CODE	94074679	RC (IN)	167.2
SW (IN)	21.7	RIM REC	W 18 L
OD (IN)	55.6	ECE	E11-106R-008830
SLR (IN)	25.6		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35
30	4500	5030	5160	5690	6150	6350	6610
25	4870	5450	5590	6160	6660	6880	7160
20	5220	5830	5990	6600	7130	7370	7670
15	5410	6050	6210	6840	7400	7650	7960
12	6000	6700	6880	7580	8200	8470	8820
10	6540	7300	7480	8260	8930	9230	9600
5	7310	8170	8380	9240	9990	10320	10750
5 FORESTRY SERVICE	-	-	-	-	-	-	8820
0 FORESTRY SERVICE	-	-	-	-	-	-	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.