


# SKID POWER SK

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>12 - 16.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | ÎNCĂRCĂTOR COMPACT   |
| <b>VERSION</b>      | IMPLEMENT  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 130 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94055746 | <b>RC (IN)</b> | 95.8            |
| <b>SW (IN)</b>  | 12.3     | <b>RIM REC</b> | 9.75            |
| <b>OD (IN)</b>  | 32.5     | <b>ECE</b>     | E11-106R-003568 |
| <b>SLR (IN)</b> | 14.8     | <b>PR</b>      | 12              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>80</b> |
| 25               | 4190      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.