


# SR 234

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>VF 445/50 R 22.5</b>   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  RADIAL                |
| <b>MACHINERY</b>    | HEUPRESSE / ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE /<br>ANHÄNGER / LANDWIRTSCHAFTLICHE<br>GERÄTE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 167 D   |



## ABMESSUNGEN US STANDARD

|                 |          |                 |                  |
|-----------------|----------|-----------------|------------------|
| <b>USA-CODE</b> | 94512799 | <b>RIM REC</b>  | 14.00            |
| <b>OD (IN)</b>  | 40.1     | <b>ECE</b>      | E11-106R-0010963 |
| <b>SLR (IN)</b> | 17.8     | <b>TRA CODE</b> | I2               |
| <b>RC (IN)</b>  | 120.1    |                 |                  |

## LOAD CAPACITY (LBS/TIRE)

|                |           |
|----------------|-----------|
| <b>MPH/PSI</b> | <b>98</b> |
| 40             | 12000     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.