


AGRIMAX TERIS

TIRE SIZE	IF 710/75 R 32 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ХЛОПКОУБОРОЧНАЯ МАШИНА
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	183 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94059249	RC (IN)	222.6
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	74.0	RIM ALT	DW 23 B
SLR (IN)	33.5	ECE	E11-106R-005025

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	20	23	29	35	41	46
30	7530	8870	10230	12730	13890	15240	16400	17940	19300
25	7530	8870	10230	12730	13890	15240	16400	17940	19300
20	8060	9500	10950	13630	14870	16310	17560	19200	20650
10 CYC*	11670	13760	15850	19740	21540	23630	25430	27820	29900
5 CYC*	13550	15970	18410	22920	25000	27440	29520	32300	34720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.