


FL 635

TIRE SIZE	620/40 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BALPRESS / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	154 D



DIMENSIONER IS STANDARD

SW (MM)	625	RIM REC	AG 20.00
OD (MM)	1068	ECE	E4-106R-002399
SLR (MM)	470	SRI	500
RC (MM)	3249		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1095	1250	1405	1745	1985	2290	2600	2835	3110	3415
65	1200	1370	1540	1915	2175	2515	2850	3115	3415	3750
50	1455	1660	1865	2320	2635	3045	3455	3770	4135	4540
40	1635	1865	2095	2605	2960	3420	3880	4235	4645	5100
25	1900	2165	2430	3025	3440	3970	4505	4920	5395	5925
10	2160	2465	2770	3445	3915	4525	5130	5605	6145	6750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.