


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>210/95 R 18</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 108 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |               |
|-----------------|----------|----------------|---------------|
| <b>USA CODE</b> | 94028672 | <b>RC (IN)</b> | 101.0         |
| <b>SW (IN)</b>  | 8.4      | <b>RIM REC</b> | W 7           |
| <b>OD (IN)</b>  | 33.7     | <b>RIM ALT</b> | W 6           |
| <b>SLR (IN)</b> | 15.2     | <b>ECE</b>     | E4-106R-00634 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 1040 | 1190 | 1370 | 1540 | 1720 | 1900 | 2050 | 2210 |
| <b>25</b>   | 1040 | 1190 | 1370 | 1540 | 1720 | 1900 | 2050 | 2210 |
| <b>20</b>   | 1110 | 1280 | 1470 | 1650 | 1840 | 2040 | 2200 | 2360 |
| <b>5 LT</b> | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |
| <b>5 HT</b> | 1110 | 1280 | 1470 | 1650 | 1840 | 2040 | 2200 | 2360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.